



DMS1

Baseboard profile

 **eubiqueurope** | www.eubiqueurope.com

All images are included for illustrative purposes. The products can be modified. All photographic images published in the brochure are the exclusive property of Eubiq Europe Srl therefore it is forbidden to reproduce, permanent or temporary, adaptation, communication to the public, dissemination, distribution to the public without the estimate and express consent of the copyright holder on the same photographic images.

DMS1

Baseboard profile | With corner caps



DMS1 has been designed to make the baseboard functional and elegant. DMS1 is designed for simple cable management in all environments. The angular corner caps, the quick coupling system and the wide range of multimedia connectors available make this profile extremely versatile and adaptable to any setting: both public and private.

Technical data

Electrical

Voltage: 250V single phase

Current: 32 A maximum at 25 ° C *room temperature*

Frequency: 50/60 Hertz

Materials

DMS1 Material: Aluminum

Insulation material: Polycarbonate

Dimensions and weights

Overall dimensions: 150 mm x 40 mm (*width. x prof.*)

Weight: 1,73 kg (*per meter*)



DMS1

Baseboard profile | Electric canalization



Museum

The installation of this profile does not require any masonry work, therefore it is excellent for ancient structures.

Canalization

The DMS1 profile can be used as an electric channeling system.

